



panel monitor

Together with the family of Vesa Monitor, the MONITORS for panel mounting complete the range of solutions for HMI devices. SCE solutions include a range of touchscreen monitors with displays from 12" to 21.5" Wide, and some with QWERTY membrane keyboard integrated on the front panel.

TECHNICAL FEATURES

	12KT	15T	15KT	15WT	17T	18WT	21WT
FRONT PANEL FEATURES							
Front Frame	Anodized aluminium, 6mm thickness, IP65 protection degree						
LCD Display	12.1", TFT, 16.2M colors	15.1", TFT, 16.2M/ 256K colors		15.6" Wide, TFT, 16.2M colors	17.1", TFT, 16.7M colors	18.5" Wide, TFT, 16.2M colors	21.5" Wide, TFT, 16.7M colors
Resolution	800x600 (SVGA) optional 1024x768 (XGA)	1024x768 (XGA)		1920x1080 (Full HD)	1280x1024 (SXGA)	1366x768 (WXGA)	1920x1080 (Full HD)
Touchscreen	Optional: analog resistive touchscreen, 5/8 wires / PCT Touchscreen True Flat for the 15WT						
Keyboard (integrated on front panel)	Alphanumeric, Membrane, QWERTY layout, 81 keys, F1 - F12, direction and control keys, IP65	No	Alphanumeric, Membrane, QWERTY layout, 81 keys, F1 - F12, direction and control keys, IP65	No	No	No	No
Touchpad (integrated on front panel)	Integrated capacitive, 2 keys	No	Integrated capacitive, 2 keys	No	No	No	No
TECHNICAL FEATURES							
Display Area	246(W)mm x 185(H)mm (diagonal 12.1")	304(W)mm x 228(H)mm (diagonal 15.1")		344(W)mm x 194(H)mm (diagonal 15.6")	338(W)mm x 270(H)mm (diagonal 17.1")	410(W) x 230(H)mm (diagonal 18.5")	477(W)mm x 268(H)mm (diagonal 21.5")
Calibration	OSD (on screen display) buttons on the back						
Contrast	700:1				1000:1		5000:1
Brightness	450cd/mq LED-backlight				400cd/mq LED-backlight		350cd/mq LED-backlight
Video Interface	VGA cable supplied + DVI						
ELECTRICAL FEATURES							
Power Supply	110/220Vac IN, min. 40W or 12Vdc IN, min. 40W / optional 24Vdc IN						
MECHANICAL FEATURES							
Case	Galvanized steel structure. Panel or Standard VESA 75/100 mounting						
Dimensions Frontal panel (W x H x D)	(430 x 325 x 8) mm	(415 x 315 x 6) mm	(483 x 399 x 8) mm	(460 x 285 x 6) mm	(483 x 399 x 6) mm	(500 x 320 x 6) mm	(564 x 355 x 6) mm
Cut Out (W x H x D)	(397 x 298 x 53) mm		(451 x 373 x 61) mm	(446 x 276 x 61) mm	(451 x 373 x 61) mm	(480 x 300 x 50) mm	(544 x 336 x 50) mm
ACCESSORIES							
Supports	Optional: Arms with VESA Standard 75/100						
Display	Optional Industrial transfective display 12.1", wide range temperature for sunlight readable application						
ENVIRONMENTAL CONDITIONS							
Operating Temperature	+0°C +60°C						
Relative Humidity	Max 80% (non-condensing)						

PRODUCT DETAILS



INFORMATION REQUEST

Do you have doubts or need more information? Write to web@sce.it

DOWNLOAD

Download the catalogue "[Industrial PC & Monitor](#)"