

monitor inox

The Monitor INOX is particularly suitable for applications in food & beverage, chemical and pharmaceutical markets. The proposed solutions include a range of monitors with displays from 17 " to 24" Wide. The stainless-steel chassis and a true flat frontal with Multitouch Projected Capacitive touchscreen, assure protection from dirt, water, scratches and an intensive use by the operator, even in the harshest areas.

TECHNICAL FEATURES

	INOX 17T	INOX 21WT	INOX 24WT
	FRONT PANEL FEATURES		
Front Frame	INOX Steel, Back IP65 protection / Frontal IP67 Protection		
LCD Display	17,1", TFT, 16,7M colors	21,5" Wide, TFT, 16,7M colors	23,8" Wide, TFT, 16,7M colors
Resolution	1280x1024 (SXGA)	1920x1080 (Full HD)	1920x1080 (Full HD)
Touchscreen	Projected Capacitive Touch (PCT), USB internal interface with multi-touch technology		
	TECHNICAL FEATURES		
Display Area	338(W)mm x 270(H)mm (diagonal 17.1")	477(W)mm x 268(H)mm (diagonal 21,5")	527(W)mm x 296(H)mm (diagonal 23,8")
Calibration	OSD (on screen display) buttons on the back		
Contrast	1000:1	5000:1	1000:1
Brightness	400cd/mq LED-backlight	300cd/mq LED-backlight	400cd/mq LED-backlight
Video Interface	VGA cable supplied + DVI		
	ELECTRICAL FEATURES		
Power Supply	9-36Vdc or 110/220Vac IN		
	MECHANICAL FEATURES		
Case	VESA Mounting, Desktop Mounting, INOX Steel, IP65 protection		
Dimensions (W x H x D)	(460 x 370 x 60) mm	(580 x 360 x 60) mm	(650 x 396 x 60) mm
Weight	9 kilos	13 kilos	15 kilos
	ACCESSORIES		
Supports	Optional: Arms with VESA Standard 75/100		
External Keyboard	Stainless steel industrial keyboard with USB interface, 83 keys, layout QWERTY, stainless steel trackball 38mm. Included with inox support, to be mounted in ergonomic way on VESA MONITOR		
	ENVIRONMENTAL CONDITIONS		
Operating Temperature	-20°C +50°C		
Relative Humidity	Max 80% (non-condensing)		

PARTICOLARI PRODOTTO







RICHIEDI INFORMAZIONI

Hai dubbi o perplessità sul prodotto? Scrivi a web@sce.it

DOWNLOAD

Scarica il catalogo completo "Industrial PC & Monitor"