

monitor vesa 21wt

Specifically designed for tools machine, the VESA 21WT MONITOR combines design with reliability, thanks to an anti-shock polyurethane case and the True Flat front panel with Projected Capacitive Touchscreen, ideal for an intensive interaction by the operator. It can be installed on VESA arms or vertical supports for floor installation and combined with embedded systems as the SHOT PC series.

TECHNICAL FEATURES

	21WT
	FRONT PANEL FEATURES
Front Frame	3mm tempered glass True Flat
LCD Display	21,5" WIDE, TFT, 16,7M colors
Resolution	1920x1080 (Full HD)
Touchscreen	Projected Capacitive Touch (PCT), USB internal interface with Multi-Touch technology
	TECHNICAL FEATURES
Display Area	477(W)mm x 268(H)mm (diagonal 21.5")
Calibration	OSD (on screen display) buttons on the back
Contrast	5000:1
Brightness	350cd/mq LED-backlight
Video Interface	VGA double shielding cable supplied + DVI
	ELECTRICAL FEATURES
Power Supply	Internal 110/220 Vac IN
	MECHANICAL FEATURES
Case	Black Polyurethane Protective Case, Impact Resistant. Standard VESA 75/100 mounting
Dimensions (W x H x D)	(540 x 335 x 75) mm
	ACCESSORIES
Supports	Optional: Arms with VESA Standard 75/100
External Keyboard	Optional: Stainless Steel Industrial Keyboard with USB interface, 83 keys, layout QWERTY, stainless steel trackball 38mm
Floor Stand	Optional: Vertical Alloyed Alluminium structure
	ENVIRONMENTAL CONDITIONS
Operating Temperature	+0°C +60°C
Relative Humidity	Max 80% (non-condensing)

PRODUCT DETAILS



INFORMATION REQUEST

Do you have doubts or need more information? Write to web@sce.it

DOWNLOAD

Download the catalogue "Industrial PC & Monitor"