special vesa 21wt

PC VESA 21WT is the SCE solution for data collection, directly in the production area. It can be installed either on VESA arms or on floor mounting devices, combined with external membrane keyboard with trackball and supports for RFID readers and barcode readers. The 21.5" Wide display with Full HD resolution allows a complete visualization of synoptic and graphic pages, with a Projected Capacitive Touchscreen that simplifies the use of the operator, providing protection from dust, scratches and usury. The design is compact, fanless and suitable to integrate an internal UPS that protects your PC from any blackout or mains problem.

TECHNICAL FEATURES

	VESA 21WT
	FRONT PANEL FEATURES
Front Frame	3mm tempered glass True Flat
LCD Display	21,5" WIDE, TFT, 16,7M colors
Resolution	1920x1080 Full HD, 350cd/m2, LED backlight, 5000:1
Touchscreen	Projected Capacitive Touch (PCT), USB internal interface with Multi-Touch technology
	SYSTEM FEATURES
CPU	CPU AMD GX-412HC 1.2-1.6GHz QUAD CORE Fanless
RAM Memory	2x DDR3 1333 SDRAM (SO-DIMM) - max. 16 GB
	MASS STORAGE
HDD/SSD	1x 2,5" Hard Disk Drive SATA Interface (also with extractable drawers) or Solid State Disk 2,5" SATA interface or integrated M-SATA
	I/O INTERFACES
Serial	up to 3x RS232
Ethernet	2x Realtek RLT8111C 10/100/1000 Mbps
USB	4x USB 2.0 rear; up to 2x USB 3.0 (on board)
VGA/HDMI/DVI	1x VGA / 1x DVI-I
PS2	1x Keyboard + 1x Mouse
WiFi	Optional: Mini PCI Express WLAN 802.11 b/g/n with antenna
Video	Radeon™ R3E 267/350MHz
	EXPANSION SLOTS
Mini PCIe	1x Mini PCIe
	ELECTRICAL FEATURES
Power Supply	19-24Vdc IN, 5A or External power adapter 110/220Vac IN
	MECHANICAL FEATURES

Case	VESA Mounting, Aluminum, IP65 Protection
Dimensions (W x H x D)	(565 x 355 x 87) mm
	ACCESSORIES
Operating Systems	MS Windows 7 / 8 / 10 IOT CBB / 10 IOT LTSB, MS Windows 7 Embedded, Linux
UPS	Optional: Integrated UPS function
External Keyboard	Industrial silicon keyboard with USB interface, 83 keys, layout QWERTY, integrated trackball 38mm. Included with aluminum alloy mechanical support, to be mounted in ergonomic way on floor stand
Floor Stand	Optional: Alloyed Alluminum structure / External Keyboard support
	ENVIRONMENTAL CONDITIONS
Operating Temperature	+0°C +50°C
Storage Temperature	-30°C +70°C
Relative Humidity	Max 80% (non-condensing)

PRODUCT DETAILS

INFORMATION REQUEST

Do you have doubts or need more information? Write to web@sce.it

DOWNLOAD

Download the catalogue "Industrial PC & Monitor"