INDUSTRIAL PC AND MONITOR



inox

The PC INOX is particularly suitable for applications in food & beverage, chemical and pharmaceutical markets. The stainless-steel chassis and a true flat frontal with Multitouch Projected Capacitive touchscreen, assure protection from dirt, water, scratches and an intensive use by the operator, even in the harshest areas.

TECHNICAL FEATURES

	INOX 17T	INOX 21WT	INOX 24WT
	FRONT PANEL FEATURES		
Front Frame	INOX Steel, Back IP65 protection / Frontal IP67 protection		
LCD Display	17,1", TFT, 16,7M colors	21,5" WIDE, TFT, 16,7M colors	23,8" WIDE, TFT, 16,7M colors
Resolution	1280x1024 (SXGA), 400cd/m2, LED backlight, 1000:1	1920x1080, 350cd/m2, LED backlight, 5000:1	1920x1080, 450cd/m2, LED backlight, 5000:1
Touchscreen	Projected Capacitive Touch (PCT), USB internal interface with Multi-Touch Technology		
	SYSTEM FEATURES		
CPU	CPU Intel Bay Trail E3845 Quad Core 1.91GHz Fanless / CPU Intel Apollo Lake Pentium N4200 Quad Core Fanless		
RAM Memory	1x 4GB DDR3 1333 SDRAM (SO-DIMM) integrated on board / Socket version up to 8GB		
	MASS STORAGE		
HDD/SSD	Solid State Disk 2,5" SATA or integrated M-SATA		
	I/O INTERFACES		
Serial	up to 3x RS232 + 1x RS422/485		
Ethernet	2x Realtek RLT8111C 10/100/1000 Mbps		
USB	3x USB 2.0 + 1x USB 3.0		
VGA/HDMI/DVI	1x VGA + 1x HDMI		
PS2	1x Keyboard + 1x Mouse optional		
WiFi	Optional: High power 802.11 b/g/n WIFI, dual antenna		
Video	Bay Trail Graphic Chip integrated, up to 512MB shared memory / Intel Apollo Lake 9th Generation Graphics Engine		
Digital I/O	Hardware digital Input & Output, 4x IN and 4x OUT optional		
	ELECTRICAL FEATURES		
Power Supply	9-36Vdc IN or 110/220Vac IN		
	MECHANICAL FEATURES		
Case	VESA Mounting, Desktop Mounting, INOX Steel, IP65 Protection		
Dimensions (W x H x D)	(460 x 370 x 60) mm	(580 x 360 x 60) mm	(650 x 390 x 60) mm
	ACCESSORIES		
Operating Systems	MS Windows 7 / 8 / 10 IOT CBB / 10 IOT LTSB, MS Windows Embedded, Linux		
UPS	Line Interactive UPS, up to 2000VA (Connection cable and software included)		
External Keyboard	Stainless steel industrial keyboard with USB interface, 83 keys, layout QWERTY, stainless steel trackball 38mm. Included with aluminum alloy mechanical support, to be mounted in ergonomic way on PC M-RED METAL		
Floor Stand	Optional: Alloyed Alluminum structure / External Inox Keyboard support		
	ENVIRONMENTAL CONDITIONS		

Operating Temperature	-20°C +50°C
Relative Humidity	Max 80% (non-condensing)

PRODUCT DETAILS



INFORMATION REQUEST

Do you have doubts or need more information? Write to web@sce.it

DOWNLOAD

Download the catalogue "Industrial PC & Monitor"