

PANEL MONITOR

Insieme alla famiglia di Monitor Vesa, i MONITOR A PANNELLO completano la gamma di soluzioni per l'interazione uomo-macchina. La gamma comprende Monitor con display LCD touchscreen da 12" fino a 21", passando per i modelli con tastiera QWERTY a membrana, integrata sulla parte frontale.

SPECIFICHE PRODOTTO

	12KT	15T	15KT	15WT	17T	18WT	21WT
	FRONT PANEL FEATURES						
Front Frame	Anodized aluminium, 6mm thickness, IP65 protection degree						
LCD Display	12,1", TFT, 16,2M colors	15,1", TFT, 16,2M/ 256K colors		15,6" Wide, TFT, 16,2M colors	17,1", TFT, 16,7M colors	18,5" Wide, TFT, 16,2M colors	21,5" Wide, TFT, 16,7M colors
Resolution	800x600 (SVGA) optional 1024x768 (XGA)	1024x768 (XGA)		1920x1080 (Full HD)	1280x1024 (SXGA)	1366x768 (WXGA)	1920x1080 (Full HD)
Touchscreen	Optional: analog resistive touchscreen, 5/8 wires / PCT Touchscreen True Flat						
Keyboard (integrated on front panel)	Alphanumeric, Membrane, QWERTY layout, 81 keys, F1 - F12, direction and control keys, IP65	No	Alphanumeric, Membrane, QWERTY layout, 81 keys, F1 - F12, direction and control keys, IP65	No	No	No	No
Touchpad (integrated on front panel)	Integrated capacitive, 2 keys	No	Integrated capacitive, 2 keys	No	No	No	No
	TECHNICAL FEATURES						
Display Area	246(W)mm x 185(H)mm (diagonal 12.1")	304(W)mm x 228(H)mm (diagonal 15.1")		344(W)mm x 194(H)mm (diagonal 15,6")	338(W)mm x 270(H)mm (diagonal 17.1")	410(W) x 230(H)mm (diagonal 18,5")	477(W)mm x 268(H)mm (diagonal 21.5")
Calibration	OSD (on screen display) buttons on the back						
Contrast	700:1				1000:1		5000:1
Brightness	450cd/mq LED-backlight					400cd/mq LED-backlight	350cd/mq LED-backlight
Video Interface	VGA cable supplied + DVI						
	ELECTRICAL FEATURES						
Power Supply	110/220Vac IN, min. 40W or 12Vdc IN, min. 40W / optional 24Vdc IN						
	MECHANICAL FEATURES						
Case	Galvanized steel structure. Panel or Standard VESA 75/100 mounting						
Dimensions Frontal panel (W x H x D)	(430 x 325 x 8) mm	(415 x 315 x 6) mm	(483 x 399 x 8) mm	(460 x 285 x 6) mm	(483 x 399 x 6) mm	(500 x 320 x 6) mm	(564 x 355 x 6) mm
Cut Out (W x H x D)	(392 x 297 x 53) mm		(453 x 376 x 61) mm	(448 x 278 x 61) mm	(453 x 376 x 61) mm	(482 x 302 x 50) mm	(546 x 338 x 50) mm
	ACCESSORIES						
Supports	Optional: Arms with VESA Standard 75/100						
Display	Optional Industrial transflective display 12,1", wide range temperature for sunlight readable application						
	ENVIRONMENTAL CONDITIONS						
Operating Temperature	+0°C +60°C						
Relative Humidity	Max 80% (non-condensing)						

PARTICOLARI PRODOTTO







RICHIEDI INFORMAZIONI

Hai dubbi o perplessità sul prodotto? Scrivi a web@sce.it

DOWNLOAD

Scarica il catalogo completo "Industrial PC & Monitor"