



MONITOR M-RED

I MONITOR della famiglia M-RED METAL coniugano l'affidabilità di un prodotto industriale alla bellezza di un design studiato e personalizzabile. Installati a fine linea su bracci mobili o piantane, grazie alla predisposizione posteriore ad un attacco VESA standard, sono tipicamente abbinati ai nostri PC della serie SHOT. Le soluzioni proposte comprendono una gamma di monitor con display dal 12" al 19" Wide, di colore rosso, nero o azzurro o personalizzabile con i colori aziendali, tastiere in acciaio inox, bracci e piantane abbinabili.

SPECIFICHE PRODOTTO

	12T	15T	17T
FRONT PANEL FEATURES			
Front Frame	Alloyed aluminium, IP65 protection degree		
LCD Display	12,1", TFT, 16,2M colors	15,1", TFT, 16,2M/ 256K colors	17,1", TFT, 16,7M colors
Resolution	800x600 (SVGA) optional 1024x768 (XGA)	1024x768 (XGA)	1280x1024 (SXGA)
Touchscreen	Optional: analog resistive touchscreen, 5/8 wires		
TECHNICAL FEATURES			
Display Area	246(W)mm x 185(H)mm (diagonal 12.1")	304(W)mm x 228(H)mm (diagonal 15.1")	338(W)mm x 270(H)mm (diagonal 17.1")
Calibration	OSD (on screen display) buttons on the back		
Contrast	700:1		1000:1
Brightness	450cd/mq LED-backlight		400cd/mq LED-backlight
Video Interface	VGA cable supplied + DVI		
ELECTRICAL FEATURES			
Power Supply	External power adapter 110/220Vac IN, min. 40W or 12Vdc IN, min. 40W / optional 24Vdc IN		
MECHANICAL FEATURES			
Case	Alloyed aluminium structure (black, red or blue colors). Standard VESA 75/100 mounting		
Dimensions (W x H x D)	(312 x 265 x 74,5) mm	(380 x 294 x 74,5) mm	(418 x 342 x 75) mm
ACCESSORIES			
Supports	Optional: Arms with VESA Standard 75/100		
External Keyboard	Stainless steel industrial keyboard with USB interface, 83 keys, layout QWERTY, stainless steel trackball 38mm. Included with aluminum alloy mechanical support, to be mounted in ergonomic way on VESA MONITOR		
Display	Optional Industrial transfective display 12,1", wide range temperature for sunlight readable application including adjustable sun visor		
ENVIRONMENTAL CONDITIONS			
Operating Temperature	+0°C +60°C		
Relative Humidity	Max 80% (non-condensing)		

PARTICOLARI PRODOTTO



RICHIEDI INFORMAZIONI

Hai dubbi o perplessità sul prodotto? Scrivi a web@sce.it

DOWNLOAD

Scarica il catalogo completo "[Industrial PC & Monitor](#)"