

MONITOR VESA 21WT

Specificatamente studiato per macchine utensili, il MONITOR VESA 21WT coniuga design ad affidabilità, grazie ad un case in poliuretano antiurto abbinato al frontale True Flat con Touchscreen Capacitivo Retroproiettato, ideale per un'interazione intensiva da parte dell'operatore. Può essere installato su bracci di supporto VESA o piantane da pavimento ed abbinato a PC da interno quadro, della serie SHOT.

SPECIFICHE PRODOTTO

	21WT
	FRONT PANEL FEATURES
Front Frame	3mm tempered glass True Flat
LCD Display	21,5" WIDE, TFT, 16,7M colors
Resolution	1920x1080 (Full HD)
Touchscreen	Projected Capacitive Touch (PCT), USB internal interface with Multi-Touch technology
	TECHNICAL FEATURES
Display Area	477(W)mm x 268(H)mm (diagonal 21.5")
Calibration	OSD (on screen display) buttons on the back
Contrast	5000:1
Brightness	350cd/mq LED-backlight
Video Interface	VGA double shielding cable supplied + DVI
	ELECTRICAL FEATURES
Power Supply	Internal 110/220 Vac IN
	MECHANICAL FEATURES
Case	Black Polyurethane Protective Case, Impact Resistant. Standard VESA 75/100 mounting
Dimensions (W x H x D)	(540 x 335 x 75) mm
	ACCESSORIES
Supports	Optional: Arms with VESA Standard 75/100
External Keyboard	Optional: Stainless Steel Industrial Keyboard with USB interface, 83 keys, layout QWERTY, stainless steel trackball 38mm
Floor Stand	Optional: Vertical Alloyed Alluminium structure
	ENVIRONMENTAL CONDITIONS
Operating Temperature	+0°C +60°C
Relative Humidity	Max 80% (non-condensing)

PARTICOLARI PRODOTTO







RICHIEDI INFORMAZIONI

Hai dubbi o perplessità sul prodotto? Scrivi a web@sce.it

DOWNLOAD

Scarica il catalogo completo "Industrial PC & Monitor"