

ASSIST L

Famiglia di PC dalla straordinaria compattezza, gli ASSIST L si caratterizzano per le numerose interfacce I/O integrate a bordo che garantiscono prestazioni elevate con configurazioni Fanless e CPU a basso assorbimento. La gamma comprende PC con display LCD touchscreen da 8" a 21", passando per i modelli con tastiera a membrana QWERTY integrata.

SPECIFICHE PRODOTTO

	L8	L10	L12	L15	L15W	L17	L18,5W	L21W	L24W
	FRONT PANEL FEATURES								
Front Frame	White alloyed aluminium, 6mm thickness, IP65 protection degree								
LCD Display	8", TFT	10,4", TFT	12,1", TFT	15,1", TFT	15,6", TFT	17,1", TFT	18,5" WIDE, TFT	21,5" WIDE, TFT	23,8" WIDE, TFT
Resolution	800x600 (SVGA), 400cd/m2, LED backlight, 500:1	800x600 (SVGA), 400cd/m2, LED backlight, 700:1	800x600 (SVGA) optional 1024x768 (XGA), 450cd/m2, LED backlight, 700:1	1024x768 (XGA), 450cd/m2, LED backlight, 700:1	1920x1080 (FullHD), 400cd/m2, LED backlight, 500:1	1280x1024 (SXGA), 400cd/m2, LED backlight, 1000:1	1366x768 400cd/m2, LED backlight, 1000:1, or 1920x1080 350cd/m2, 5000:1	1920x1080 (FullHD), 450cd/m2, LED backlight, 5000:1	1920x1080 (FullHD), 450cd/m2, LED backlight, 5000:1
Touchscreen	Optional: analog resistive touchscreen, 5 wires / PCAP Multitouch True Flat								
Keyboard (integrated on front panel)	No	No	No	No	No	No	No	No	No
Touchpad (integrated on front panel)	No	No	No	No	No	No	No	No	No
	SYSTEM FEATURES								
CPU	CPU Bay Trail J1900 2.0 GHz / CPU Apollo Lake Pentium N4200 2.0 GHz / CPU Skylake I5-6300U 3.0GHz / CPU Atom X6413 3.0GHz / CPU I7-1185GRE 4.4GHz								
RAM Memory	1x SO-DIMM DDR3 - max. 32 GB								
	MASS STORAGE								
HDD/SSD	up to 2x 2,5" Hard Disk Drive SATA Interface (also with extractable drawers) or Solid State Disk 2,5" SATA interface or integrated M-SATA								
	I/O INTERFACES								
Serial	up to 3x RS232 + 1x RS232/422/485								
Ethernet	2x Realtek RLT8111C 10/100/1000 Mbps								
USB	up to 4USB								
VGA/HDMI/DVI	1x VGA / HDMI / DVI depending on MB								
Extra port	Additional 1x USB or + 1x COM								
WiFi	Optional: Mini PCI Express WLAN 802.11 b/g/n with antenna								
Video	Intel Integrated Graphics chipset								
Digital I/O	Optional: Hardware digital Input & Output, 4x IN and 4x OUT								
	EXPANSION SLOTS								
Mini PCIe	1x Mini PCIe								

	ELECTRICAL FEATURES								
Power Supply	9-36Vdc IN, optional 110/220Vac IN with external power adapter 60W								
	MECHANICAL FEATURES								
Case	Panel Mount, Steel nickel treatment								
Dimensions Frontal panel (W x H x D)	(220x180x4) mm	(305x230x6) mm	(335x270x6) mm	(415x315x6) mm	(460x285x6) mm	(473x390x6) mm	(500x320x6) mm	(564x355x6) mm	(640 x 402 x 6) mm
Cut Out (W x H x D)	(188x167x65) mm	(278x197x65) mm	(315x 250x85) mm	(392x297x85) mm or (370x295x85) mm	(448x278x85) mm or (410x255x85) mm	(453x375x85) mm or (435x335x85) mm	(482x302x85) mm	(546x338x85) mm	(620x382x85) mm
	ACCESSORIES								
Operating Systems	MS Windows 7 Professional Or Embedded / 10 IOT LTSB or LTSC, MS Windows 11, Linux								
UPS	Optional: Integrated UPS function with internal lithium battery								
	ENVIRONMENTAL CONDITIONS								
Operating Temperature	+0°C +60°C								
Relative Humidity	Max 80% (non-condensing)								

PARTICOLARI PRODOTTO













PC ASSIST L 15T-17T PC ASSIST L 15WT PC ASSIST L 12KT-15KT PC ASSIST L connectors PC ASSIST L 15T-17T back

RICHIEDI INFORMAZIONI

Hai dubbi o perplessità sul prodotto? Scrivi a web@sce.it