

SPECIAL VESA 21WT

Il PC VESA 21WT è la proposta di SCE per la raccolta dati, in ambiente di produzione e/o fine linea. Può essere installato sia su bracci di supporto VESA che su piantana, completo di tastiera con trackball e supporti per lettori badge e barcode. Il display 21,5" Wide Full HD permette una visualizzazione completa e definita di sinottici e pagine grafiche, con un Touchscreen Capacitivo Retroproiettato, che semplifica l'utilizzo da parte dell'operatore, garantendo protezione da polveri, graffi e usura. Il design è compatto, Fanless e adatto ad integrare un UPS interno, che protegge il PC da sbalzi o interruzioni di corrente.

TECHNICAL FEATURES

	VESA 21WT
	FRONT PANEL FEATURES
Front Frame	3mm tempered glass True Flat
LCD Display	21,5" WIDE, TFT, 16,7M colors
Resolution	1920x1080 Full HD, 350cd/m2, LED backlight, 5000:1
Touchscreen	Projected Capacitive Touch (PCT), USB internal interface with Multi-Touch technology
	SYSTEM FEATURES
CPU	CPU AMD GX-412HC 1.2-1.6GHz QUAD CORE Fanless
RAM Memory	2x DDR3 1333 SDRAM (SO-DIMM) - max. 16 GB
	MASS STORAGE
HDD/SSD	1x 2,5" Hard Disk Drive SATA Interface (also with extractable drawers) or Solid State Disk 2,5" SATA interface or integrated M-SATA
	I/O INTERFACES
Serial	up to 3x RS232
Ethernet	2x Realtek RLT8111C 10/100/1000 Mbps
USB	4x USB 2.0 rear; up to 2x USB 3.0 (on board)
VGA/HDMI/DVI	1x VGA / 1x DVI-I
PS2	1x Keyboard + 1x Mouse
WiFi	Optional: Mini PCI Express WLAN 802.11 b/g/n with antenna
Video	Radeon™ R3E 267/350MHz
	EXPANSION SLOTS
Mini PCIe	1x Mini PCIe
	ELECTRICAL FEATURES
Power Supply	19-24Vdc IN, 5A or External power adapter 110/220Vac IN
	MECHANICAL FEATURES

Case	VESA Mounting, Aluminum, IP65 Protection
Dimensions (W x H x D)	(565 x 355 x 87) mm
	ACCESSORIES
Operating Systems	MS Windows 7 / 8 / 10 IOT CBB / 10 IOT LTSB, MS Windows 7 Embedded, Linux
UPS	Optional: Integrated UPS function
External Keyboard	Industrial silicon keyboard with USB interface, 83 keys, layout QWERTY, integrated trackball 38mm. Included with aluminum alloy mechanical support, to be mounted in ergonomic way on floor stand
Floor Stand	Optional: Alloyed Alluminum structure / External Keyboard support
	ENVIRONMENTAL CONDITIONS
Operating Temperature	+0°C +50°C
Storage Temperature	-30°C +70°C
Relative Humidity	Max 80% (non-condensing)

PRODUCT DETAILS



INFORMATION REQUEST

Do you have doubts or need more information? Write to web@sce.it

DOWNLOAD

Download the catalogue "Industrial PC & Monitor"